



INVESTOR IN PEOPLE

The Patent Office
 Concept House
 Cardiff Road
 Newport
 South Wales
 NP10 8QQ


BEST AVAILABLE COPY

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 23 February 2005



The
**Patent
Office**

14JAN04 EB65056-3 D01038
P01/7700 0.00-0400687.0 CHEQUE

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

Request for grant of a patent

See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

51325/P710562GB/AJC

2. Patent application number

(The Patent Office will fill in this part)

13 JAN 2004

0400687.0

3. Full name, address and postcode of the or of each applicant *(underline all surnames)*

InVivo Technology Limited
1 Redman Court
Bell Street
Princes Risborough
Buckinghamshire
HP27 0AA
United Kingdom

08666463001

Patents ADP number *(if you know it)*

If the applicant is a corporate body, give the country/state of its incorporation

England and Wales

4. Title of the invention

Bladder Mapping

5. Name of your agent *(if you have one)*

"Address for service" in the United Kingdom to which all correspondence should be sent *(including the postcode)*

WITHERS & ROGERS
Goldings House
2 Hays Lane
London
SE1 2HW

Patents ADP number *(if you know it)*

1776001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and *(if you know it)* the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? *(Answer 'Yes' if:*

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

YES

Patents Form 1/77


9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form -

Description 9

Claim(s) -

Abstract -

Drawing (s) 2 + 2 

10. If you are also filing any of the following, state how many against each item.

Priority documents -

Translations of priority documents -

Statement of inventorship and right to grant of a patent (Patents Form 7/77) -


Request for preliminary examination and search (Patents Form 9/77) -

Request for substantive examination (Patents Form 10/77) -

Any other documents (please specify) -

11.

I/We request the grant of a patent on the basis of this application.


Signature

Date 12/01/2004

12. Name and daytime telephone number of person to contact in the United Kingdom

Adrian J Chettle

01926 336111

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least six weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500 505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

P710562GB

Bladder Mapping

This invention relates to human bladder mapping, and to apparatus for treatment of the human bladder.

5

As is well-known, the human bladder accumulates urine for periodic release at a convenient place and time. Instability of the bladder may result in uncontrolled leakage, so called stress incontinence, which can be both unpleasant and embarrassing. Instability may be caused for example by infection, a poorly functioning sphincter, or

10

by spasm of the bladder.

In the latter case it is known that the bladder wall is a focal area of electrical activity within the human body, and that abnormal electrical bursts may occur. This electrical activity, which cannot be felt, is considered to be one cause of bladder instability.

15

According to a first aspect of the invention, there is provided apparatus for detecting the location of electrical activity in the wall of a human bladder.

20

Upon detection of electrical activity, a treatment of the location may prevent subsequent activity, or may mitigate the effect thereof.

25

Detection apparatus may be external or internal to the human body, and comprise for example a spaced array of devices adapted to detect electrical activity, and to permit the location of said activity to be determined by mathematical techniques such as for example triangulation.

In the case of external apparatus, the devices may be arranged below the bladder, for example on or in a flat support, and in a triangular formation.

The apparatus may however comprise a detector adapted to be introduced into the bladder via the urethra, and having a connector to the exterior whereby the location of electrical activity in the wall of the bladder can be determined.

- 5 The detector may for example be a contact device adapted to touch the interior wall of the bladder and thereby detect electrical activity. In one embodiment the device comprises a cage having a plurality of detection sites thereon, the cage being insertable through the urethra in a collapsed form and being expandable within the bladder into contact with the wall thereof. A suitable reversible expanding mechanism may rely
10 upon relative telescopic movement of inner and outer members of connector passing to the exterior. In a preferred embodiment the cage is open so that expansion and contraction is unimpeded by fluid within the bladder.

- In use such a device contacts the wall of the bladder at a plurality of places. Electrical
15 activity within the bladder is detected at one or more detection sites, and information concerning the location of this activity passes to the exterior via the connector. Each detection site may for example be adapted to sense a transient voltage, and thus to indicate a location or path of electrical activity by the size of the voltage detected at one or more sites. Where several sites detect substantially simultaneous electrical activity,
20 triangulation techniques may be used to determine the location of the source.

- An expandable detector is typically a regular three-dimensional body in the expanded state, and has uniformly distributed detection sites thereon. In one embodiment the detector resembles a sphere in the expanded state, and has a plurality of arcuate arms
25 extending between opposite poles, one of which poles is coupled to the exterior connector. In the collapsed state the arms lie in close proximity to each other so as to have a small overall cross-section and thus be adapted for insertion through the urethra.

- The expanded envelope of such a device is preferably selected to suit the approximate
30 size of the bladder into which it is to be inserted. However it is envisaged that the bladder may itself be stretched by the device so as to ensure more uniform contact by the detection sites thereof.

The number of detection sites are selected to allow the location of electrical activity to be determined with reasonable certainty. In the case of the spherical device noted above, eight equispaced arms may be provided, each with eight equispaced detection sites thereon. The greater the number of detection sites, the more precise can be location of the source.

The apparatus may further include means to permit the orientation thereof to be determined. Such means are not essential, as will become apparent, but may be useful in determining the actual location of electrical activity in relation to other body organs. Approximate orientation may be determinable from the connector, and for example a longitudinally extending mark thereon. Orientation means may also comprise for example one or more identifiable detection sites adapted to be stimulated from the exterior, or an asymmetric array of detection sites.

15

In a preferred embodiment said connector may include one or more lumens to permit access from the exterior. A lumen may for example permit the bladder to be filled with liquid so as to become distended. A full bladder may be more suitable for application of the detector, and is also more likely to stimulate bursts of electrical activity.

20

The same or another lumen may be used for the introduction of medicaments.

The connector is preferably relatively stiff so as to permit easy insertion thereof through the urethra and to permit some steering of the detector. However a lumen of the connection may be adapted to take a relatively stiff guide member so as to ease passage thereof. The guide member may be curved so as to place the detector in a desired position within the bladder.

25

Where lumens are provided for fluid, suitable valve means are typically required so as to prevent voiding of the bladder. Such valve means may be at the exterior in the form of e.g. a tap or clamp, or may be at the interior in the form of e.g. a self closing slit diaphragm.

30

The apparatus may further include a tubular introducer via which the device may be inserted into the bladder. Such an introducer may itself be inserted after enlargement of the urethra by a dilator, and typically has an exterior valve to prevent voiding of the bladder when in place. The introducer may have one or more side ports adapted to permit insertion of the apparatus therethrough, and other tubes or guides, as may be required.

In an alternative embodiment the detector may be of the non-contact kind adapted to detect electrical activity in the wall of the bladder whilst being located at a distance therefrom. As will be appreciated such a non-contact device may be somewhat smaller than a contact type and thus less difficult to pass through the urethra. A suitable non-contact type may be spherical. Like the contact type described above eight equispaced arms may connect the poles, each arm having eight detection sites thereon. Being smaller, this non-contact detector may comprise a balloon insertable in the deflated state, and inflatable by injection of fluid through a connecting lumen. Typical inflation means comprise a syringe for injecting a precise volume of physiologically acceptable solution into the balloon.

In order to maintain such a balloon or other non-contact detector at the approximate centre of the bladder, a stiff or stiffened connector is preferably used. Alternatively the non-contact detector may be provided with one or more spacing members on the surface thereof and movable from a stowed to a deployed condition. In the case of an inflatable detector, the spacing members may deploy automatically as inflation occurs, and be adapted to restow as the detector is deflated, or as it is withdrawn from the bladder.

The spacing members may for example comprise arms or loops on the surface of an inflatable detector and adapted to stand up on inflation, or may themselves each comprise an inflatable soft tube.

The spacing members need not all contact the wall of the bladder provided that the detector is stabilised.

The detection apparatus may be passive in the sense that it acts as an antenna capable of detecting electrical activity at a distance. Alternatively the detection apparatus may include transmission apparatus adapted to generate a field in the vicinity of the bladder, and detectors adapted to detect distortions of the field which are a consequence of electrical activity in the wall of the bladder.

According to a second aspect of the invention there is provided a method of introducing the detector into a human bladder comprising the steps of contracting the detector into a form having a substantially cylindrical envelope, introducing the detector through the urethra by means of a connector attached to the detector, and expanding the detector in the bladder by means of said connector. Means for expanding the detector may be mechanical, such as relatively telescopic connector components or fluid actuated, for example by introduction of liquid into an inflatable member.

Several kinds of detector for mapping electrical activity in the heart are known, such as detectors being introduced internally via a blood vessel, and permitting an image of a heart chamber to be created using computer techniques. One such detector is made by Endocardial Solutions Inc. under the name 'Ensight'.

According to a third aspect, the invention provides for the use of apparatus for mapping electrical activity in the heart, for mapping electrical activity in the human bladder.

Such apparatus is preferably internal, and is introduced into the bladder via the urethra, instead of via a blood vessel to the heart. The apparatus preferably includes a lumen adapted to permit filling of the bladder from the exterior.

According to a fourth aspect, the invention provides apparatus for mapping electrical activity in the heart, for mapping electrical activity in the wall of the bladder.

Preferably this application is of the kind intended for introduction through a blood vessel into the heart, and adapted for introduction through the urethra into the bladder.

Apparatus for the bladder has a relatively short connector as compared with apparatus intended for the heart, and accordingly signal transmission difficulties and signal attenuation are reduced. Furthermore a large diameter connector is possible because the urethra is both relatively short, and relatively expandable as compared with a blood vessel. Moreover the external opening is natural rather than artificial, and accordingly the device can be adapted for insertion requirements with greater ease, as compared with blood vessels where some means of sealing the blood vessel opening must additionally be provided.

According to a fifth aspect, the invention provides apparatus for ablation of the bladder from the interior thereof, and comprising an ablation tool adapted to be introduced into the bladder via the urethra, and means operable on command to ablate the wall of the bladder. The ablation tool may for example comprise an energy source relying on heat (radio frequency or laser) or cold (cryogenic).

Such ablation apparatus is known in relation to treatment of e.g. arrhythmia in the wall of the heart muscle, and acts by disrupting the surface of the muscle so as to change the response thereof to bursts of electrical activity. The ablation may for example scar the surface of the heart muscle so as to prevent electrical impulses following an undesirable path.

According to a sixth aspect, the invention provides apparatus for ablating the internal surface of heart muscle, for ablating the internal surface of the human bladder.

Such apparatus is introduced via the urethra instead of via a blood vessel.

Ablation apparatus typically comprises a relatively stiff wire having a bend at the distal end, and an ablation tool at the tip. After insertion into the bladder, the tip is adapted to

be steered internally to any desired region by the use of external control apparatus of a conventional kind. Such apparatus may rotate the wire, and change the insertion depth.

5 The tip of the ablation apparatus is preferably adapted to be detectable, for example by being electrically active, whereby its location can be detected by a suitable detector in the vicinity of the bladder. Accordingly the ablation tool can be manoeuvred to the site of electrical activity within the bladder, and operated to ablate the site.

10 In a preferred embodiment an ablation tool is used in conjunction with apparatus for detecting electrical activity in the bladder so as to treat bladder instability. The ablation tool is preferably introduced along the connector of an internal apparatus, and preferably within a lumen thereof.

15 According to a seventh aspect, the invention provides combination apparatus for heart mapping and ablation, for use in the treatment of human bladder instability.

Other features of the invention will be apparent from the following description of a preferred embodiment shown by way of example only in the accompanying drawings, in which Fig. 1 is a schematic illustration of a detector.

20

Fig. 1 shows schematically a somewhat distended bladder 10 connected to the exterior of the human body 11 by a urethra 12. An inflatable detector 13 is passed through the urethra in a collapsed state, and inflated (as illustrated) when in the bladder by injection of a precise volume of saline solution.

25

The detector 13 is coupled to a relatively stiff connector 14 which incorporates an inflation lumen and permits the position of the detector to be adjusted. In use the detector is positioned substantially at the 3-dimensional centre of the bladder as illustrated, at a spacing of 4-5 cm from the bladder wall.

30

The surface of the detector 13 comprises a series of equispaced wires 15 coupled at the poles. Each wire has four detection sites 16 thereon, which may be formed by laser removal of insulation.

- 5 A non-contact detector of this kind is known for mapping electrical activity in the wall of the heart, and similar techniques can be used for mapping electrical activity in the bladder wall. The sensitivity and range of the detector may of course require adjustment using conventional techniques.
- 10 Thus a burst of electrical activity 17 is in use detected by several sites 16, and computer techniques are used to identify the location of the burst, by reference to, for example, the relative strength of the signal detected at each of several sites. Suitable electrical connections to the exterior are provided via the connector 14. The sites 16 may also be adapted to detect the location of electrical tracking along and through the bladder wall,
- 15 by for example continual real time sampling of the sites 16.

Mapping of electrical activity is a useful precursor to diagnosis and treatment of bladder instability.

- 20 Fig. 2 illustrates a bladder 10 into which an ablation device 21 is introduced via the urethra 12. The device typically has a small r.f. heat source 22 at the tip thereof, and can be actuated to scar the site of a burst of electrical activity 17.

- In order to position the heat source 22, the device 21 can be moved back and forth in the urethra, and rotated. It may also be possible to bend and unbend the distal portion, using known techniques, so as to ensure that the entire surface of the bladder wall can be reached. In practice the tip 22 may be adapted to emanate an electrical signal, and the device 21 may be used in conjunction with the detector 13 so as to locate the tip accurately on the bladder wall. It will be understood that suitable techniques are known
- 30 from use of similar equipment in the treatment of the heart.

Bursts or single spikes of electrical activity can occur spontaneously, and as the bladder is stretched. Accordingly in a preferred embodiment of the invention a lumen is provided whereby the bladder can be filled via the invention in order to stimulate electrical activity for diagnosis and treatment.

5

Typically a volume of physiologically acceptable liquid, such as saline solution, is passed through the urethra in a controlled manner for example from an elevated reservoir, and via a one-way valve at the exterior side. The lumen may be incorporated in the connector 14, or may lie at the side thereof. It will be understood that the
10 detector is activated during filling of the bladder so as to detect electrical activity as the bladder wall is stretched.

Fig.3 illustrates how the cross section of a connector 14 may appear in the preferred embodiment, and having an electrical connection 31 for transmitting mapping
15 information, an inflation lumen 32 for the detector, and a filling lumen 33 for saline solution. The inflation lumen is necessarily closed at the distal end by the balloon, but the filling lumen 33 is open. The filling lumen may pass through the balloon to the distal side, and thus provide for passage of a removable guide wire to stiffen the connector/balloon during insertion thereof. Such a guide wire preferably has a
20 conventional pigtail end to prevent accidental damage to the bladder wall as the device is inserted through the urethra.

At the exterior side such a combination lumen includes suitable closures, such as valves, to maintain the balloon in an inflated state, and to maintain the bladder in an
25 expanded state. Release of these valves respectively allows the balloon to deflate for withdrawal, and for the bladder to drain.

The filling lumen 32 may also be used to transfer a medicament into the bladder, for example through injection via an exterior side port.




Fig 1




Fig 2




Fig 3

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000056

International filing date: 11 January 2005 (11.01.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB
Number: 0400687.0
Filing date: 13 January 2004 (13.01.2004)

Date of receipt at the International Bureau: 17 March 2005 (17.03.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.